



COMPACT DRYERS

www.arskametalli.fi



EVEN SUITABLE FOR EXISTING BUILDINGS

Compact dryer has everything ready for the farmer. Basis for the design was a fast factory supply and easy assembly. Compact is suitable in all locations, where electricity is available – for example, in a feed storage or a machine garage.

All you need is a concrete base and enough height for the elevator. The dryer is electrified 80% ready by the manufacturer. Machinery is a Special or Magnum model.

COMPACT (S)	2,5+2	2,5+3	3,5+3	3,5+4	4,5+4
Total volume [m ³]	15,7	19,3	22,0	25,6	28,3
Heat cell volume [m ³]	6,7	6,7	9,4	9,4	12,1
Storage container volume [m ³]	7,2	10,8	10,8	14,4	14,4
Dryer height [m]	6,9	7,8	8,8	9,7	10,6
Elevator min. height [m]	9,5	10,5	11,5	12,5	13,5
Elevator [t / h] *	68	68	68	68	68
Heater [model] *	A200	A200	A200	A200	A200
Pre-cleaner [model] *	4000S	4000S	6000S	6000S	6500S
Fuse size [A] *	25	25	35	35	50

COMPACT (M)	3,5+2	3,5+3	3,5+4	4,5+4	4,5+5
Total volume [m ³]	24,1	28,6	33,1	36,7	41,2
Heat cell volume [m ³]	12,5	12,5	12,5	16,1	16,1
Storage container volume [m ³]	9,0	13,5	18,0	18,0	22,5
Dryer height [m]	7,8	8,8	9,7	10,6	11,5
Elevator min. height [m]	11,5	12,5	13,5	14,5	15,5
Elevator [t / h] *	68	68	68	92	92
Heater [model] *	A200	A200	A200	A250	A250
Pre-cleaner [model] *	6000S	6000S	6000S	6500S	6500S
Fuse size [A] *	35	35	35	50	50

* Recommendation / Other volumes also available!

TRANSPORT HEIGHT

Compact dryer is delivered as in the image. Dryer base, elevator bottom part, tipping hopper and control panel are located on top of the sturdy frame.





STANDARD EQUIPMENT

- ✓ Elevator
- ✓ Overpressure heater
- ✓ Control panel
- ✓ Pre-cleaner
- ✓ Bottom fan 1.5kW
- ✓ Bottom conveyor 1.5kW
- ✓ Tipping hopper 1x3m 1.5kW
- ✓ Service platform and ladder
- ✓ Air piping 3m
- ✓ Circulate piping


OPTIONS

- + Rain cover for tipping hopper
- + Seed Cleaner
- + Cyclone
- + GSM alarm
- + Control automation
- + Scale device
- + Additional switch for feeder
- + Rain covers for burner, elevator and pre-cleaner
- + Motored shutter for heat cell



ARSKAMETALLI OY

 Saarentaantie 33
FI-31400 Somero, Finland

 +358 2 748 9700

 posti@arskametalli.fi

© Arskametalli Oy 2021

All rights reserved. In the photos in this brochure or other publications may occur devices which are not standard equipment. Technical specifications are approximate.